



# MULTI-FUEL EXPEDITIONARY HEATERS



## KEY FEATURES

- Stainless steel combustion chamber for long life
- Supply air separate from combustion air
- Water-resistant electronic flame control box
- Preheated fuel filter allows for use in extreme temperatures
- Ruggedized aluminum frame provides protection while keeping weight low
- Stackable design for storage efficiency
- Wheels and fork pockets (HH180 only) allow for efficient field maneuverability
- Large fuel tanks for hours of continuous operation
- Durable powder coated finish
- UL Certified

SPECIFICATIONS	HH75	HH180
<b>PART NUMBER</b>	731380	731381
<b>HEAT OUTPUT</b>	75,000 BTU/H	180,000 BTU/H
<b>TANK CAPACITY</b>	11.6 gallons	17 gallons
<b>FUEL CONSUMPTION UNDER CONTINUOUS USE</b>	0.53 gallons per hour	1.27 gallons per hour
<b>FUEL REQUIREMENTS</b>	DF1, DF2, JP5, JP8 and Kerosene	DF1, DF2, JP5, JP8 and Kerosene
<b>POWER REQUIREMENTS</b>	120 VAC, 60Hz, Single Phase	120 VAC, 60Hz, Single Phase
<b>POWER USAGE</b>	3 Amps @ 120V	13 Amps @ 120V
<b>ACCESSORIES INCLUDED</b>	Exhaust Stack, Heater Ducts (2), Remote Thermostat, O&M Manual	Exhaust Stack, Heater Ducts (2), Remote Thermostat, O&M Manual

©2023 UTS Systems, LLC | Current as of July 2022 | Information subject to change without notice.